



Ziggurat

Off the road tyres.
Off the chart endurance.



STURDY, LONG-LASTING OTR TYRES FOR:

Earthmovers, Graders, Loaders, Dozers, Compactors, Container Handlers/Stackers, Underground Mining & Other Applications

[ESPAÑOL](#) | [ABOUT US](#) | [QUOTE REQUEST](#)

ZIGGURAT L-101

Download PDF



[| back to L-101 information |](#)

PNEUMATIC INDUSTRIAL TYRES

Size	P.R.	Overall	Section	Tread	Rims	Inflated	Load Capacity (kgs)								Quantity
		Diameter	Width	Depth		Pressure	Drive Wheel		Steer Wheel		Industrial Vehicles				per
		(mm)	(mm)	(mm)		(Kpa)	16km/h	24km/h	24km/h	32km/h	8km/h	16km/h	24km/h	32km/h	40HQ
5.00-8	10	468	144	12	3.50D	1000	1290	1100	955	850	955	760	705	655	3000
6.00-9	10	540	166	13	4.00E	860	1680	1515	1280	1125	1280	1010	945	875	1800
6.50-10	10	590	186	15	5.00F	790	1915	1725	1455	1280	1455	1150	1075	1000	1300
7.00-12	12	676	197	19	5.00S	860	2720	2445	2065	1815	2065	1360	1520	1415	990
7.00-12	14	676	197	19	5.00S	1000	2965	2670	2255	1980	2255	1780	1660	1540	990
7.00-15	12	762	203	19	5.50F	860	3150	2835	2395	2100	2395	1890	1760	1635	790
7.00-15	14	762	203	19	5.50F	1000	3400	3060	2585	2270	2585	2040	1910	1785	790
7.50-15	12	802	215	19	6.00G	790	3490	3140	2650	2330	2650	2095	1955	1815	690
7.50-15	14	802	215	19	6.00G	925	3640	3290	2800	2480	2800	2245	2105	1965	690
8.25-15	12	830	250	20	6.5	720	3935	3545	2990	2630	2990	2365	2205	2050	560

8.25-15	14	830	250	20	6.5	830	4255	3830	3235	2845	3235	2555	2385	2215	560
18x7-8	14	465	173	14	4.33R	900	1855	1685	1450	1295	1450	1160	1100	1040	2100
18x7-8	16	465	173	14	4.33R	1000	2130	1960	1640	1490	1640	1355	1285	1205	2100
21x8-9	14	533	203	15	6.00E	1000	2350	2115	1785	1570	1785	1405	1315	1220	1300
23x9-10	18	584	225	13	6.50F	1080	3240	2900	2485	2285	2485	1965	1875	1710	980
23x10-12	12	597	255	14	8	830	3290	2950	2495	2185	2495	1970	1835	1705	900
27x10-12	14	690	255	16	8.00G	830	3400	3035	2650	2350	2650	2140	1980	1800	700
8.15-15	14	706	231	20	7	970	3415	3075	2595	2280	2595	2050	1910	1775	600
250-15	16	735	250	20	7.5	930	4285	3855	3265	2860	3265	2575	2405	2230	570
250-15	18	735	250	20	7.5	1030	4580	4105	3470	3040	3470	2745	2560	2375	570
300-15	20	840	300	21	8	930	6575	5940	4990	4400	4990	3945	3675	3425	360
9.00-20	14	1034	259	20	7	760	5880	5285	4465	4105	4465	3520	3290	3065	250
10.00-20	16	1070	300	22	7.5	795	6765	6085	5140	4520	5140	4055	3790	3520	200
10.00-20	18	1070	300	22	7.5	900	7300	6560	5545	4875	5545	4370	4090	3800	200
12.00-20	16	1145	331	25	8.5	690	7725	6980	5895	5180	5895	4655	4345	4035	170
12.00-20	18	1145	331	25	8.5	900	8275	7500	6415	5700	6415	5175	4865	4555	170
12.00-20	24	1145	331	25	8.5	1150	9455	8680	7595	6880	7595	6355	6045	5735	170